

XiOptics is one of the few sources for fiber optic termini designed specifically for size 16 cavities found in ARINC 404 and ARINC 600 connection systems.

The 10G FP TOSA with LC Receptacle is an optical component with a high-performance ridge waveguide (RWG) Fabry-Pérot laser chip. The laser emits at 1310 nm wavelength and has been ...

With a broad range of sensor options, the Blackfly S platform is ideal for automated optical inspection, factory automation, microscopy, 3D scanning, and other imaging tasks that require a balance of ...

It is composed of software and hardware such as optical fingerprint sensor, high-speed DSP processor, high-performance fingerprint comparison algorithm, and large-capacity Flash chip. ...

It is composed of software and hardware such as optical fingerprint ...

The Hirose 6-Pin I/O Cable with an open end provides a flexible and reliable connection for industrial equipment. Compatible with various devices, it supports seamless integration for power and signal ...

1. Supplies power to SATA devices such as hard drives and optical drives 2. Provides a reliable and efficient power connection D. EPS 6-pin power connector

Shop DigiKey's large in-stock selection of Photointerrupters - Slot Type - Logic Output. View inventory, pricing and order now for same day shipping!

6-Pin DIP Zero-Cross Triac Driver Optocoupler (600 Volt Peak) MOC3061M, MOC3062M, MOC3063M, MOC3162M, MOC3163M Description The MOC306XM and MOC316XM devices consist of a GaAs ...

Secure your project with biometrics - this adorably tiny, all-in-one, optical fingerprint sensor will make adding fingerprint detection and verification super simple. It's extremely slim, with a ...

Web: <https://www.cgaroofing.co.za>