

100G CFP2 LR4/OTU4, 1310nm, 10km, DDM, LC/UPC Duplex, Single Mode, Optical Transceiver Module Specs 103.125 Gbps 10km 1310 nm LC/UPC Duplex P/N: MJ-CFP2100G-LR4 SKU: 1113102 ...

CFP2100G(2V100Ah) Charged Volume Charge Voltage Charging Current Effect of Temperature on Capacity

Soluciones y Servicios para Vial y Agro. Mecánica, Inyección e Hidráulica. Tenemos para todas las medidas para Agro, Vial, camiones y autolevadores Hacemos envíos. Consulta por tu modelo.

100GBASE-LR4 and OTN CFP2 Transceiver Module (SMF, 1310nm, 10km, LC, DOM) SPECIFICATION

These small, modular optical interface transceivers offer a convenient and cost-effective solution for an array of applications in the data center, campus, metropolitan-area access and ring network, storage ...

The Generic compatible CFP2 optical transceiver module is designed for use in 100 Gigabit Ethernet links over 10 km of single-mode fiber and complies with the CFP MSA CFP2 Hardware Specification ...

It works to interconnect equipment with CFP2 model optical interfaces/ports to exchange and transmit data of up to 100Gbps over 10km. Through an optical cable or cord using 2 fibers, you will be able to ...

This product has acquired the relevant product qualification (s)/license (s) of certain applicable country/countries. View more.

CFP2100G (2V100Ah) Dimensions The Relationship for Open Circuit Voltage and Residual Capacity (25°C)

Designed to transmit and receive data in both directions on a single fiber for 100G and beyond. Provides an operationally efficient and cost-effective way for telecommunications and cable operators to ...

Web: <https://www.cgaroofting.co.za>