

According to DIN EN 61518 the manifold-transmitter interface is applicable for a max. allowable (Working) Pressure (PS) of 413 bar*3 (6,000 psi) and a maximum allowable Temperature (TS) of ...

L-com's simplex metal ST couplers are designed for mounting in rectangular holes used for simplex SC couplers. This series features either bronze or ceramic alignment sleeves to meet your specific ...

A process interface valve fitted with an injection probe and a check valve allows fluids to be dispersed into the process stream while providing protection against backflow of process fluids.

For standard stainless steel flange adapters, select an ordering number from the table on page 3. Build a special-order flange adapter by combining the designators in the sequence shown below.

It features an FC interface on one end and an ST interface on the other, compatible with both single-mode and multimode fibers. The metal construction ensures durability and stability, suitable for ...

This ST Duplex Universal Fiber Optic Coupler / Adapter with works with both singlemode and multimode fiber and is designed to couple together ST patch cables / connectors.

Explore 316/316L stainless steel flange adapters that meet ASME, DIN EN, and JIS standards. Available in a range of flange sizes and pressure classes.

Learn how flange adaptors work, where to use them, and how to install--fast, reliable pipeline connections for water and industrial systems.

With the advantages of low price, easy push-pull operation, low insertion loss, good compression strength, etc, it has been widely used since the 1990s with only the ST connector competing with it.

These adapters offer a robust and dependable solution for linking FC and ST connectors, making them invaluable in laboratory settings or extensive network infrastructures.

Web: <https://www.cgaroofing.co.za>